



Indoor

DS-2CD753F-E(I) 2MP Vandal Resistant Network Dome Camera

- Up to 2 Megapixel resolution
- H.264/MPEG4/MJPEG Video Compression with high compression ratio
- Progressive scan CMOS
- Up to 32 GB SD/SDHC card local storage
- Two-way audio
- PoE
- Conforms to ONVIF and PSIA



Unit: mm



Specifications

		DS-2CD753F-E	DS-2CD753F-EI	
Camera	Image Sensor	1/3" Progressive Scan CMOS		
	Min. Illumination	0.5 Lux @ (F1.2, AGC ON), 0.1 Lux @ (F1.2, AGC ON, sensitivity × 5) DS-2CD753F-EI: 0 Lux with IR		
	Shutter Time	1/25 s to 1/100,000 s		
	Lens	2.7 - 9 mm @ F1.2		
		Angle of view: 101° - 30.4°		
	Lens Mount	Φ14		
	Auto Iris	DC drive		
Angle Adjustment	Pan: 0° - 360°, Tilt: 0° - 75°, Rotation: 0° - 360°			
Day & Night	Electronic	IR cut filter with auto switch		
Compression Standard	Video Compression	H.264 / MPEG4 / MJPEG		
	Bit Rate	32 Kbps - 16 Mbps		
	Audio Compression	G.711		
	Dual Stream	Yes		
Image	Max. Image Resolution	1600 × 1200		
	Frame Rate	60 Hz: 15 fps (1600 × 1200), 30 fps (1280 × 720)		
	Image Setting	Saturation, Brightness, Contrast adjustable through client software or web browser		
Network	Local Storage	Built-in SD/SDHC slot, up to 32 GB		
	Alarm Trigger	Motion detection, Network disconnect, IP address conflict, Storage exception		
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP		
	Security	Password protection, Watermark		
	System Compatibility	ONVIF, PSIA, CGI		
Interface	Audio Input	1-ch microphone input, 3.5 mm mini-jack		
	Audio Output	1-ch 3.5 mm audio interface (Line level, 600 Ω)		
	Communication Interface	1 RJ45 10 M/100 M Ethernet port and 1 RS-485 interface		
	Alarm Input	2		
	Alarm Output	2		
General	Reset Button	Yes		
	Operating Conditions	-10 °C - 60 °C (14 °F - 140 °F); Humidity 90% or less (non-condensing)		
	Power Supply	12 V DC ± 10%; PoE (802.3af)		
	Power Consumption	Max. 4.5 W	Max. 6.5W	
	Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10		
	IR Range	-	Up to 60 feet	
	Dimension (Dia.xH)	Φ 140 × 114 mm (Φ 5.51" × 4.49")		
Weight	1400 g (3.09 lbs)			

Accessories

DS-1227ZJ (Flush Mount), DS-1229ZJ (Wall Mount)